



SportsPlay™

We Put the Value in Play!

SportsPlay Equipment, Inc.
500 Delmar Blvd, Ste G, St. Louis, MO 63124
(314) 389-4140 (800) 727-8180 Fax (314) 389-9034
www.sportsplayinc.com

HD TIRE SWING SPECIFICATIONS

Swing legs and Top rail shall be 8 gauge 3 1/2" O.D. These are produced in a patented in line triple zinc flo-coating process that provides a smooth shiny uniform appearance with up to 25% greater corrosion resistance than galvanized schedule 40 pipe, along with greater strength and lighter weight for comparable sizes.

Swing end and center fittings shall be fabricated from 7 gauge 2 7/8" O.D. flo-coated tubing coated with powder-coated paint.

Heavy Duty Swivel swing hanger will hold over 5000 lbs. and turn 360 degrees without tangling.

Plastic Tire shall be one piece rotationally molded plastic.

Chain shall be hot dip galvanized 4/0 chain link. Material diameter is .218 inches.

Nominal inside link dimensions 1.29" x .38" with a working load limit of 670 pounds.

Swing seats shall be 6" x 24" molded rubber with steel plate inserts. Hardware shall be zinc coated. S-Hooks shall be 3/8" O.D., 3" long zinc coated.

SportsPlay Modern Swings meet the CPSC (Consumer Product Safety Commission) playground safety guidelines, the ASTM (American Society of Testing Materials) playground safety standards and have been certified by IPEMA (International Playground Equipment Manufacturers Association).